

# OSBORN BELT DRESSING 76206

## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

#### Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	OSBORN BELT DRESSING 76206
Product Code	M-5714

#### Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Belt dressing
Uses Advised Against	None
Company Identification	Osborn 2350 Salisbury Road North Richmond, IN 47374 USA
Telephone	(765) 965-5333
Fax	(765) 935-0212
E-Mail (competent person)	<a href="mailto:marketsupport@osborn.com">marketsupport@osborn.com</a>

#### Emergency telephone number

Emergency Phone No.	<b>Transportation Emergency:</b> CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	-------------------------------------------------------------------------------------------------------------

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)	Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1
-----------------------------	-------------------------------------------------------------------------------------------

#### Label elements

Hazard Symbol



Signal word(s)

**DANGER**

Hazard Statement(s)

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure:  
Central Nervous System, Route: Inhalation  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.

Precautionary Statement(s)

# OSBORN BELT DRESSING 76206

Use only outdoors or in a well-ventilated area.

Do not breathe mist/vapours/spray.

Wear protective gloves/eye protection.

Wash hands and exposed skin after use.

Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

**Other hazards:**

None

**Additional Information:**

None

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
n-Hexane	40 - 50	110-54-3	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Repr. 2; H361 Skin Irrit. 2; H315 STOT SE 3; H336 STOT RE 2; H373
Proprietary polymers	0 - 20	Trade Secret	Not classified as dangerous for supply/use.
Acetone	10 - 15	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Propane	10 - 15	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Butane	10 - 15	106-97-8	Flam. Gas 1; H220 Liquefied gas; H280

**Additional Information – None**

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May be harmful if swallowed and enters airways.

**Indication of any immediate medical attention and special treatment needed**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

# OSBORN BELT DRESSING 76206

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.  
Do not use water jet.

### Special hazards arising from the substance or mixture

Pressurised container: May burst if heated

### Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Avoid contact with skin and eyes. Avoid breathing vapors.

### Environmental precautions

Prevent liquid entering sewers, basements and work pits.

### Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

### Reference to other sections

None

### Additional Information

None

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use product in a well-ventilated area only. Avoid contact with skin and eyes. Avoid breathing vapors.

### Conditions for safe storage, including any incompatibilities

- Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50 °C / 122 °F.

- Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

### Specific end use(s)

Belt dressing

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#
Acetone	67-64-1	1000	500	-----	750	^NIC
n-Hexane	110-54-3	500 ppm	50 ppm*	-----	-----	*Skin

#Assure minimum oxygen content of work atmosphere; ^NIC = Notice of Intended Changes (ACGIH®)

### Recommended monitoring method

NIOSH 1300 (Ketones I); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1501 (Hydrocarbons, Aromatic)

### Exposure controls

### Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

# OSBORN BELT DRESSING 76206

## Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely. Check with protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

## Environmental Exposure Controls

None known

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Aerosol
Color	Colorless
Odor	mildly pungent, somewhat aromatic
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. $95 \times 10^4$ (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	<20 cSt
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
<b>Other information</b>	Not available

## SECTION 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical stability</b>	Stable.
<b>Possibility of hazardous reactions</b>	None anticipated.
<b>Conditions to avoid</b>	Avoid contact with heat and ignition sources.
<b>Incompatible materials</b>	Strong oxidizing agents
<b>Hazardous decomposition product(s)</b>	Carbon monoxide, Carbon dioxide, Acrid smoke

# OSBORN BELT DRESSING 76206

## SECTION 11: TOXICOLOGICAL INFORMATION

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

### Information on toxicological effects

n-Hexane (CAS No. 110-54-3):

**Acute toxicity**

Oral: LD50 ≈16 g/kg-bw (May be fatal if swallowed and enters airways.)

Dermal: LD50 >2 g/kg-bw. rabbit

Inhalation: LC50 > 17600 mg/m<sup>3</sup> (Vapor), 24-hr. rat (May cause drowsiness or dizziness.)

**Irritation/Corrosivity**

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

**Sensitization**

It is not a skin sensitizer.

**Repeated dose toxicity**

LOAEL: 37973 mg/kg (101 days, oral, rat, CNS effects)

NOAEL: 1135 mg/kg (101 days, oral, rat, CNS effects)

NOAEC: 1760 mg/m<sup>3</sup> (90 day, inhal., female mice, nasal lesions)

LOAEC: 3000 ppm (12 hr a day for 16 weeks, inhal., rat, CNS effects)

**Carcinogenicity** (By analogy with similar materials)

NOEL: 31736 mg/m<sup>3</sup> (2 years, inhal. Oncogenic effects)

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

**Mutagenicity**

There is no evidence of mutagenic potential.

**Reproductive toxicity**

Studies in animals have shown that repeated exposures produce adverse reproductive effects.

Acetone (CAS No. 67-64-1)

**Acute toxicity**

Oral LD50 = 5800 mg/kg (rat)

Dermal LD50 >15800 mg/kg (rabbit)

Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.

**Irritation / Corrosivity**

Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.

**Sensitisation**

It is not a skin sensitiser.

**Repeated dose toxicity**

Oral NOAEL = 900 mg/kg/day (rat) (90-days)

Inhalation NOAEL ≥ 19,000 ppm (rat)

**Carcinogenicity**

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

**Mutagenicity**

Negative

**Toxicity for reproduction**

Negative

**Other information**

None known.

Propane (CAS# 74-98-6):

**Acute toxicity**

Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)

**Irritation/Corrosivity**

No evidence of irritant effects from normal handling and use.

**Sensitisation**

It is not a skin sensitiser.

**Repeated dose toxicity**

NOAEC: ≥19678 mg/m<sup>3</sup> (28-day, rat, Systemic effects)

LOAEC: 21641 mg/m<sup>3</sup> (28-day, rat, effects: Body weight)

**Carcinogenicity**

No data. It is unlikely to present a carcinogenic hazard to man.

**Mutagenicity**

There is no evidence of mutagenic potential.

**Reproductive toxicity**

None anticipated

# OSBORN BELT DRESSING 76206

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

#### n-Hexane (CAS# 110-54-3):

Short term	LC50 (96 hour): >1000 µg/L ( <i>Oryzias latipes</i> ) LC50 (48 hour): 45 mmol/m3 ( <i>Daphnia magna</i> , mortality) EC50 (96 hour): 2.66% ( <i>C. pyreniodosa</i> )
Long Term	NOELR (28 days) 2.8 mg/l ( <i>Fish</i> ) QSAR NOELR (21 days): 4.88 mg/l ( <i>Daphnia magna</i> ) QSAR NOEL (96 hour) 2.077 mg/l (Algae) QSAR

### Persistence and degradability

Readily biodegradable.

### Bioaccumulative potential

The product has no potential for bioaccumulation.

### Mobility in soil

Not available

### Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

### Other adverse effects

None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

## SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
n-Hexane	110-54-3	45	5000
Acetone	67-64-1	10	5000

SARA 311/312 - Hazard Categories:

Fire  Sudden Release  Reactivity  Immediate (acute)  Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
n-Hexane	110-54-3	25 - 30

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

# OSBORN BELT DRESSING 76206

## California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	-----	-----

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: May 25, 2015

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

### Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure:

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.