

## **SAFETY DATA SHEET**

## SECTION 1: IDENTIFICATION

Product identifier used on the label:

SILITE SILICONE RTV-- CLEAR Product Name:

Stock No.: 17100

Other means of identification:

Recommended use of the chemical and restrictions on use:

 $\underline{\hbox{Chemical manufacturer address and telephone number:}}\\$ 

Manufacturer Name: ITW Performance Polymers

30 Endicott Street Address: Danvers, MA 01923

(978) 777-1100 General Phone Number:

Emergency phone number:

(800) 424-9300 Emergency Phone Number:

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-9300

# SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

Not applicable. Signal Word:

GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.. .

Hazards not otherwise classified that have been identified during the classification process:

Emergency Overview: CAUTION! Harmful. Irritant.

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may

cause lacrimation, conjunctivitis, corneal damage and permanent injury.

Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling.

Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible

tissue destruction.

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
Dimethyl siloxane, hydroxy-terminated	70131-67-8	80 - 90 by weight	
Ethyltriacetoxysilane	17689-77-9	1 - 10 by weight	
Inert material	N/A	1 - 10 by weight	

SILITE SILICONE RTV-- CLEAR Stock No. 17100 Revision:: 10/05/2015

Methyltriacetoxysilane 4253-34-3 1 - 10 by weight

### SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers. Get immediate medical attention

Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Skin Contact:

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained Inhalation:

personnel. Seek immediate medical attention

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person.

## SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to Fire Fighting Instructions:

minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible,

contain fire run-off water.

# SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

 $\underline{\text{Methods and materials for containment and cleaning up:}}$ 

Absorb spill with inert material (e,g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Avoid personal contact and breathing vapors or mists. Ventilate area. Use proper personal protective Spill Cleanup Measures:

equipment as listed in Section 8.

Reference to other sections:

Other Precautions: Pump or shovel to storage/salvage vessels.

### SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor, aerosol or mist.

Hygiene Practices: Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat and incompatible materials. Keep

container tightly closed when not in use.

# SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

**EXPOSURE GUIDELINES:** 

Appropriate engineering controls:

SILITE SILICONE RTV-- CLEAR Revision:: 10/05/2015

Stock No. 17100

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general **Engineering Controls:** 

ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance

Individual protection measures:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Eye/Face Protection:

Skin Protection Description:  $We ar appropriate \ protective \ gloves \ and \ other \ protective \ apparel \ to \ prevent \ skin \ contact. \ Consult$ 

of the personal protective equipment.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower

safety station.

Only established PEL and TLV values for the ingredients are listed. Notes:

### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State Appearance: Paste. Odor: Vinegar.

>300°F (148.8°C) **Boiling Point:** Melting Point: Not determined.

Specific Gravity: 1.04 Solubility: negligible. Vapor Density: >1 (air = 1)

Vapor Pressure: Not determined.

Percent Volatile: <5

<1 (butyl acetate = 1) Evaporation Rate:

Not determined.

Molecular Formula: Mixture Molecular Weight:

Flash Point: >250°F (121.1°C) Flash Point Method: Tag closed cup. (TCC)

Lower Flammable/Explosive Limit: Not determined. Upper Flammable/Explosive Limit: Not determined. Auto Ignition Temperature: Not determined. **VOC Content:** Not determined.

9.2. Other information:

Percent Solids by Weight >95

## SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.

**Incompatible Materials:** 

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

# SECTION 11: TOXICOLOGICAL INFORMATION

## TOXICOLOGICAL INFORMATION:

SILITE SILICONE RTV-- CLEAR Revision:: 10/05/2015

#### $\underline{\textbf{Dimethyl siloxane, hydroxy-terminated}}:$

RTECS Number: VW3168750

Skin: Administration onto the skin - Rabbit LD50 : >16 mL/kg [Kidney, Ureter, Bladder - Other changes

Nutritional and Gross Metabolic - Other changes]

Inhalation: Inhalation - Rat LC50 : >8750 mg/m3/7H [Lungs, Thorax, or Respiration - Other changes]

Ingestion: Oral - Rat LD50 : >15400 mg/kg [Sense Organs and Special Senses (Eye) - Ptosis Behavioral -

Somnolence (general depressed activity) Kidney, Ureter, Bladder - Urine volume increased]

Methyltriacetoxysilane:

RTECS Number: VV4500000

Ingestion: Oral - Rat LD50 : 2060 mg/kg [Details of toxic effects not reported other than lethal dose value]

### SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

### SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous

waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

guidelines.

RCRA Number: None.

# SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Non regulated.

DOT UN Number: Not applicable.

DOT Hazard Class: Not applicable.

DOT Packing Group: Not applicable.

# SECTION 15: REGULATORY INFORMATION

 $\underline{\textbf{Safety, health and environmental regulations specific for the product:}}$ 

TSCA Inventory Status: All the constituents of this product are TSCA listed or exempt from listing.

<u>Dimethyl siloxane, hydroxy-terminated</u>:

TSCA Inventory Status: Listed
Canada DSL: Listed

**Ethyltriacetoxysilane:** 

TSCA Inventory Status: Listed
Canada DSL: Listed

<u>Methyltriacetoxysilane</u>:

TSCA Inventory Status: Listed
Canada DSL: Listed

Canadian Regulations. WHMIS Hazard Class(es): D2B

All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms:

1

# SECTION 16: ADDITIONAL INFORMATION

**HMIS Ratings**:

HMIS Health Hazard: 1 HMIS Fire Hazard: 1 HMIS Reactivity: 1 HMIS Personal Protection:

Health Hazard Fire Hazard Reactivity **Personal Protection** 

October 05, 2015 SDS Revision Date: SDS Revision Notes: "GHS Update"

SDS Format:

SDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our knowledge and belief at the date of its

publication but we cannot accept liability for any loss, injury or damage which may result from its use. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment.

Copyright© 1996-2018 Enviance. All Rights Reserved.

SILITE SILICONE RTV-- CLEAR Revision:: 10/05/2015