

Steel Lockers

Two Person Lockers

Ample storage for two people in a space only 15" wide!

- Each occupant has a full-length coat compartment with two hooks, plus a full-width opening at top for small articles
- Left door and upper compartment work together as do the right-hand door and lower compartment
- Coat compartment doors have handles with padlock attachments
- Built-in locks are optional
- Shipped K.D. (knocked down)
- Locker opening dimensions:
Small – 15"w x 18"d x 9"h,
Large – 7½"w x 18"d x 54"h

Ideal for the Healthcare Industry!

Add optional antimicrobial finish for protection against the touch transfer of bacteria on locker surfaces.

See page 113 for details on how antimicrobial protection works.



Features



Small upper door is released with a latch inside the corresponding coat compartment door.

Example

Order one **No. 5407** & receive this one section: **one frame wide (four locker openings for two people).**

Order one **No. 5407-3** & receive this one section: **three frames wide (twelve locker openings for six people).**



W x D x H* Overall Size	No. of Frames	No. of Openings	K.D. Cat. No.	Set Up Cat. No.
15" x 18" x 72"	1	4	5407	5407SU**
45" x 18" x 72"	3	12	5407-3	5407-3SU**

*Heights shown do not include legs – add 6" to height for legs.

**Call Customer Service for lead time.

Color Selection

In Stock

DD Dove Gray

PP Putty



Additional colors are available upon request



ADA REQUIREMENTS FOR LOCKERS

1. Doors must be able to be opened without a twisting or clapping motion. The standard test for compliance is if the door can be opened with closed fingers.

A recessed handle with a lockbar or single point is compliant.
2. The locker bottom must be a minimum of 15" from the finished floor. This is accomplished by locating a shelf 12" from the bottom of the locker. Additional shelves can be purchased separately, contact Lyon Customer Service. The shelf is acceptable as the locker bottom and when the locker is placed on a minimum 3" base the shelf/bottom is a minimum of 15" from the finished floor.
3. The locker shelf or hooks can not exceed 48" from the finished floor. The shelf and hooks can be relocated during set-up.

Contact Lyon Customer Service for more ADA product specs, and project support on choosing the best locker solution for your project.

