



Nitrile

## Distinct color to mask stains for special applications

- Provides firm and consistent wet grip due to fully textured design and non-foaming formula
- Distinctive black color hides stains and provides a contrasting backdrop for identifying lighter colored material
- Offers a higher tensile strength and flexibility compared to the minimum requirements as set for both ASTM D6319 and EN 455 standards
- Contains no natural rubber latex and powder-free, to help protect against type I skin allergies and irritation



### Industries

- Automotive
- Emergency Medical Services
- Laboratory
- Law Enforcement
- Life Sciences (Pharmaceutical, Biopharmaceutical & Medical Devices)
- Tattoo Artists

### Applications

- Analytical testing
- Biotechnologies
- Filtration processes
- Food processing
- Laboratory analysis and testing
- Light assembly tasks
- Light assembly of oil-coated pieces
- Light duty maintenance
- Mechanical repairs
- Paint and spray shops
- Pharmaceutical manufacturing
- Patient examination during transport on EMS vehicles
- Protection from blood and other bodily fluids

### TECHNICAL DATA SHEET:

#### PRODUCT INFORMATION:

	<b>MidKnight®</b>
<b>Material</b>	Nitrile
<b>Color</b>	Black
<b>Glove Design</b>	Ambidextrous, Powder-Free, Chlorinated, Fully Textured
<b>Cuff</b>	Beaded Cuff
<b>Manufacturing/ QMS Audit Standards</b>	ISO 13485
<b>Regulatory/Standards Compliance</b>	ASTM D6319, US QSR/FDA 510(K), MEDICAL (EXAMINATION) GRADE, COMPLIANT WITH U.S. FOOD CONTACT REGULATIONS
<b>Packaging</b>	100 Pack: 100 gloves per dispenser, 10 dispensers per shipper carton, 1000 gloves per shipper carton. 10 Pack: 10 gloves per pouch, 50 pouches per shipping carton, 500 gloves per shipping carton.
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Malaysia
<b>User Needs Segment</b>	Robust Glove - Gloves that provide added strength, durability and chemical splash protection for longer wear times.

#### PHYSICAL PROPERTIES:

	TYPICAL VALUES						TESTING METHOD
	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XXL	
Length (mm/in.)	245/9.6	245/9.6	245/9.6	245/9.6	245/9.6	245/9.6	ASTM D3767/EN 420
Average Palm Width (mm/in.)	80/3.14	86/3.38	96/3.77	107/4.21	115/4.52	118/4.64	
Freedom from Holes (Inspection level I)	1.5 AQL						ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm : 0.12) / (mil : 4.7)						ASTM D3767/EN 420
	BEFORE AGING			AFTER AGING			
Ultimate Tensile Strength	27 Mpa			14 Mpa			ASTM D 412-06a
Elongation at Break (%)	> 500			> 400			ASTM D 412-06a
Force at break (N)	10			11			EN 455-2

#### ORDERING INFORMATION:

	SIZE	5.5 - 6 XS	6.5 - 7 S	7.5 - 8 M	8.5 - 9 L	9.5 - 10 XL	10.5 - 11 XXL
MidKnight 100 glove dispenser	REORDER NO.	MK-296-XS	MK-296-S	MK-296-M	MK-296-L	MK-296-XL	MK-296-XXL
MidKnight 10 pack pouch is only available in Large					MK-296-RP		

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at 1-877-750-6110

Ansell  
111 Wood Avenue South  
Suite 210  
Iselin, NJ 08830  
USA

Ansell  
105 Lauder  
Cowansville, QC J2K 2K8  
Canada

