



Nitrile Dipped Glove

Product Sheet



Nitrile



Abrasion



Tear

GL601

Nylon + Spandex | Nitrile | Micro-Foam

EN388: 2016 – 4131X

Nitrile micro-foam palm coating // 15 gauge nylon + spandex liner (silicone free) // Good dexterity // Excellent grip in all conditions

GL601 S – 2XL

Suggested Applications

Handling Oily Parts // Warehousing // General Assembly // Automotive Components // Horticulture // General Duty

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Micro-Foam
Liner: 15 Gauge Nylon + Spandex (silicone free)
Cuff: Nylon + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

EN388: 2016 – 4131X

Abrasion	1	2	3	4		
Circular Blade Cut	1	2	3	4	5	X
Tear	1	2	3	4		
Puncture	1	2	3	4		
Cut TDM-100	A	B	C	D	E	F
Impact Rated	P	F	X			

Pyramex gloves that comply with the EN388:2003 standard can still be sold. As we move forward, we will start testing to the current 2016 standard.



Glove Sizing

The color of the binding around the cuff indicates the glove size.

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Pack: 12 pair
Case: 120 pair
Country of Origin: China