

# ALAIR®

FASHIONABLE ECONOMY SPECTACLE



PART	LENS	PART	LENS
S3210S**	 Clear	S3260S**	 Infinity Blue
S3210ST**	 Clear (Anti-Fog)	S3270S*	 Silver Mirror
S3220S**	 Gray	S3275S*	 Blue Mirror
S3230S**	 Amber	S3280S*	 Indoor/Outdoor Mirror

- Economically priced to fit any budget.
- Incredibly light, resilient & durable protective eyewear for all day wear.
- Closefitting unitary front with dual 9.5 base curvature offers wide and unobstructed vision.
- Fashionable design resembles sunglasses, suitable for both men and women.
- Scratch-resistant, hard-coated polycarbonate lens filter out more than 99.9% of harmful UV rays.

#### GENERAL SPECIFICATION

Bridge: 12mm
Closest Point Between Lens: 8mm
Closest Point Between Temple Tips: 84mm
Lens Base: 9.5 Curve
Lens Size Diagonal: 73mm
Lens Size Vertical: 42mm
Lens Thickness: 2.45mm
Overall Length (Lens-Tip): 158mm
Overall Width (Hinge-Hinge): 134mm
PD: 68mm
Weight: 22gm

**PACKAGING**

Polybag: 1 pc

Inner Box: 12 pcs

Case: 300 pcs

# ALAIR®

FASHIONABLE ECONOMY SPECTACLE

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9.5 curve lens, wrap around design with side protection
Frame	N/A	N/A
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula
Hinge	Polycarbonate	3 barrel type, integral to frame/sleeve
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S3210S	 Clear	P Z87 + U6	P Z87 +
S3210ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 +
S3220S	 Gray	P Z87 + U6 L2.5	P Z87 +
S3230S	 Amber	P Z87 + U6	P Z87 +
S3260S	 Infinity Blue	P Z87 + U6 L1.3	P Z87 +
S3270S	 Silver Mirror	P Z87 + S	P Z87 +
S3275S	 Blue Mirror	P Z87 + S	P Z87 +
S3280S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +

**LENS MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

**UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

**Visible Light Filters:**

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

**FRAME MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact