

RENDEZVOUS®

FULLY ADJUSTABLE SPECTACLES



PART

SB2810S***

SB2810ST***

SB2815S***

SB2820S***

SB2820ST**

SB2830S***

SB2840S***

SB2860S**

SB2860ST***

LENS

Clear

Clear (Anti-Fog)

Coffee

Gray

Gray (Anti-Fog)

Amber

Orange

Infinity Blue

Infinity Blue (Anti-Fog)

PART

SB2870S***

SB2875S***

SB2880S***

SCB2810S**

SCC2810S**

SCC2810ST**

SCC2870S**

SCG2810ST**

LENS

Silver Mirror

Blue Mirror

Indoor/Outdoor Mirror

Clear

Clear

Clear (Anti-Fog)

Silver Mirror

Clear (Anti-Fog)

- Temples adjust to four different lengths.
- Adjustable nose pad conforms to broad range of bridge sizes.
- Crafted from high grade polycarbonate, machined from virgin materials and formed to shape.
- Align lens angle to proper position for work application with ratcheting lens pitch adjustment.
- 9.5 base curve lens provides excellent side protection against wind and airborne particles, provides 99.9% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 9.6mm

Lens Base: 9.5 Curve

Lens Size Diagonal: 83mm

Lens Size Vertical: 45.5mm

Lens Thickness: 2.42mm

Overall Length (Lens-Tip): 54-166mm

Overall Width (Hinge-Hinge): 138mm

PD: 68mm

Weight: 28gm

Closest point between lens: 16.6mm

Closest point between temples tip: 75-76mm

PACKAGING

Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

RENDEZVOUS®

FULLY ADJUSTABLE SPECTACLES

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Contemporary design with dual-focus construction to fit contours of face
Frame	Polycarbonate	Lightweight & durable ventilation reduces chance of fogging
Side Shield	Polycarbonate	Integral to lens, provides excellent coverage
Nose Bridge	Polycarbonate	Break-through design, fully adjustable, soft touch & support, no pressure and slippage
Soft Nose Pad	PVC	
Sleeve (on temple)	Polycarbonate	Unique ratchet mechanism with length adjustable temple to create a custom fit. Slim design makes entire glass stylish & attractive
Temple		
Hinge	Polycarbonate	3 barrel type, integral to frame/ part (sleeve)
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB2810S	 Clear	P Z87 + U6	P Z87 +
SB2810ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 +
SB2815S	 Coffee	P Z87 + U6 L3	P Z87 +
SB2820S	 Gray	P Z87 + U6 L2.5	P Z87 +
SB2820ST	 Gray (Anti-Fog)	P Z87 + U6 L2.5	P Z87 +
SB2830S	 Amber	P Z87 + U6	P Z87 +
SB2840S	 Orange	P Z87 + S	P Z87 +
SB2860S	 Infinity Blue	P Z87 + U6 L1.3	P Z87 +
SB2860ST	 Infinity Blue (Anti-Fog)	P Z87 + U6 L1.3	P Z87 +
SB2870S	 Silver Mirror	P Z87 + S	P Z87 +
SB2875S	 Blue Mirror	P Z87 + S	P Z87 +
SB2880S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +
SCB2810S	 Clear	P Z87 + U6	P Z87 +
SCC2810S	 Clear	P Z87 + U6	P Z87 +
SCC2810ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 +
SCC2870S	 Silver Mirror	P Z87 + S	P Z87 +
SCG2810ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact