



**PYRAMEX**  
Perform At Your Peak™

**Venture 3®** ANSI CE CSA AUS BALLISTIC



VENTED  
FRAME



ADJUSTABLE  
NOSEPIECE



CO-INJECTED  
TEMPLES

Soft, adjustable ventilated nosepiece

Ventilated frame

Soft, adjustable co-injected rubber temples

Passes MIL-PRF 32432 High Velocity  
Impact Standards

Part No.	Black Frame
SB5710D ●●●●	Clear
PYSB5710D* ●●●●	Clear
SB5710DT ●●●●	AF Clear H2X
SB5720D ●●●●	Gray
SB5720DT ●●●●	AF Gray H2X
SB5730D ●●●●	Amber
PYSB5730D* ●●●●	Amber
SB5750SFT ●●●●	AF 5.0 IR Filter H2X
SB5760D ●●●●	Infinity Blue
SB5760SFT ●●●●	AF 3.0 IR Filter H2X
SB5770D ●●●●	Silver Mirror
SB5780D ●●●●	I/O Mirror

\*Pyramex retail packaged product



There's more to see at  
**PyramexSafety.com**

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (\*), Australian (AS/NZS 1337) (●) or Ballistic (MIL-PRF-32432) (●) standards.



**PYRAMEX**  
Perform At Your Peak™

## Venture 3®

### General Specifications

Weight: 28 gm  
 PD: 68 mm  
 Bridge: 12.8 mm  
 Lens base: 9.5 curve  
 Lens size diagonal: 82 mm  
 Lens size vertical: 46.6 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 150 - 163 mm  
 Overall width (hinge - hinge): 139.4 mm  
 Closest point between temple tips: 91 mm  
 Closest point between lens: 13.1 mm

### Materials

Lens: polycarbonate  
 Frame: polycarbonate  
 Temple tips: polycarbonate and thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Sleeve: polycarbonate  
 Nosepiece: bridge - polycarbonate and nose pad - polyvinyl chloride (PVC)  
 Side shields: polycarbonate

Part No.	Lens Marking	Frame Marking
SB5710D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5710DT	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5720D	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5720DT	P + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5730D	P + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5750SFT	P + W5	P Z87 +
SB5760D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5760SFT	P + W3	P Z87 +
SB5770D	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB5780D	P + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 +: High impact  
 S: Special purpose  
 W: Welding filter  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV  
 Visible Light Filters  
 L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Frame Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at  
**PyramexSafety.com**

(P) 800.736.8673 | (F) 901.861.4967