

TOOL CRIB OPEN GEAR LUBE

#620-1501



A heavy duty black lubricant that offers superior lubricity and adhesion to gears. Improves the gear efficiency and will not dry out or leave harmful deposits. Open Gear Lube is unaffected by salt water, detergents, and most chemicals. Performs well under extreme pressures and temperatures. An extension tube is furnished for pinpoint application.

Suggested Uses:

- Open gears
- Cams
- Slides
- Roller chains
- Slow moving bearings
- Latches
- Construction equipment

Packaging:

UPC Code	043281006972
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (426 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.75
Solids Content	49%
VOC content	40%
HAPs content	0
Storage Temperature	40-90F
Application Temperature	40-100F
Lubricity Rating	Excellent
Active Ingredient	Asphalt and Pine Tar
Appearance	Black, tacky
Operating Speed	500+ RPM
High Temperature Resistance	250F
Low Temperature Resistance	-10F
Heavy Load Capability	Extremely Heavy Loads
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

Not applicable

Gloss:

Not applicable