



Hydraulic & Jack Oil, 15 Fl Oz

No. SL2621 | Item# 1007846 | Case# 1007845

Product Description	A medium weight hydraulic oil blended of a high quality paraffinic base oil with anti-rust, anti-oxidation, anti-foam, anti-wear, and seal swell additives. It is a 20W, non-detergent oil.
Applications	Hydraulic systems and fluid drive units. May be added to existing fluids. Not for use in hydraulic brakes.
Unit Package Description	15 Ounce Bottle
Brand	Sta-Lube
Generic Description 1	Hydraulic & Jack Oil
Net Fill	15 Fl Oz
UPC Code	072213262100
Unit Dimensions	9H x 1.63W x 3.75D in
Units Per Case	12
Case Dimensions	9.75H x 8.5W x 11.5D in
Cases Per Pallet	133
Case Weight	13 lbs
I 2 of 5 Code	30072213262101
Appearance	Amber Viscous Liquid
Flash point (F)	380°F
Flash point (C)	193°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.87 to 0.89
Plastic Safe	Yes
Evaporation Rate	Slow
ISO Viscosity Grade	46
SAE Grade	20
Working Temp (F)	0 to 150°F
Working Temp (C)	-17.78 to 65.56°C
DOT Proper Shipping Name	Not Regulated

Last revised: 12/16/2020

Page 1 of 2



Chemical Solutions to Keep You Moving™

f t+ in • 800-272-8963 • crcindustries.com



VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Not Regulated

Last revised: 12/16/2020
Page 2 of 2