

PROFILE™

Ideal Combination of Performance & Value



Profile boots offer a balance of performance and price to help you look - and feel - good from any angle.

The Profile™ PVC Knee Boot Is Durable On The Outside And Comfortable On The Inside

Our Profile knee boot is formulated with high quality PVC resins and low temperature additives. The result is a boot that has good abrasion resistance and excellent flexibility in cold temperatures.

- Injection molded seamless construction provides 100% water-proof protection.
- Composite safety-toe meets ASTM F2413 M I/75 C/75 and does not transfer cold or set off metal detectors.
- Calf Relief Expansion (CRE)™ expands up to 1.5 inches for more calf comfort.
- Flexible upper material stays supple in cold temperatures to make walking easier.
- Outsole material is soft for excellent slip resistance and absorbs shock when walking.
- Cleated outsole spits out debris for excellent gripping action.
- Removable polyurethane, contour insole features three layers to wick perspiration, promote faster drying and absorb shock for all day comfort.



Cleated Outsole:
Spits out debris for great traction.



Contour Insole:
Cushioned removable polyurethane insole absorbs shock for added comfort.
Style: CI124
Sizes S-XL

CONTOUR INSOLE SIZE CHART - CI124

| Sizes: | S | M | L | XL |
|---------|-------|--------|---------|---------|
| Men's | 5 - 7 | 7 - 9 | 9 - 11 | 11 - 13 |
| Women's | 7 - 9 | 9 - 11 | 11 - 13 | |

Ideal Applications: Farm and Barn, Agriculture and Industry, Municipalities, and many Food Processing applications.

Chemical Resistance:

Fats, certain acids, alkalis, hydrocarbons, and other chemicals.



PROFILE KNEE BOOTS CLEATED OUTSOLE

| | | |
|---------|---|--------|
| ■ 51154 | Brown Upper – Crepe Sole – Ht. 15" – Plain Toe | 3 – 14 |
| ■ 51254 | Brown Upper – Crepe Sole – Ht. 15" – Composite Safety-Toe | 3 – 14 |
| ■ CI124 | Contour Insole | S – XL |

#4046 - 9/17

TINGLEY
A TRADITION SINCE 1896

ISO 9001 Certified

www.tingleyrubber.com

800•631•5498 fax 866•757•9239

