



1/2" DRIVE TURBOSOCKET® SALVAGE/DAMAGED FASTENER SOCKETS

Black Industrial Finish, Metric and SAE



TS50750



TS51551



TSFS5005



TSM5107

Product Code	Size (Inches)	A		B		C		D		E		F	
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)					
TS50750	3/4	1 21/32	1 1/16	1 1/16	23/32	1	3/4	-					
TS50812	13/16	1 21/32	1 1/8	1 1/8	23/32	1	13/16	-					
TS50875	7/8	1 21/32	1 3/16	1 3/16	23/32	1	7/8	-					
TS50937	15/16	1 21/32	1 5/16	1 5/16	23/32	1	15/16	-					
TS50100	1	1 21/32	1 11/32	1 11/32	23/32	1	1	-					

Product Code	Size (MM)	A		B		C		D		E		F	
		OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)					
TS51551	14	1 21/32	29/32	21/32	1/2	1	9/16	29/32					
TS51591	15	1 21/32	29/32	29/32	1/2	1	19/32	-					
TS51625	16	1 21/32	31/32	31/32	1/2	23/32	5/8	-					
TS51669	17	1 21/32	1	1	21/32	23/32	11/16	-					
TS51709	18	1 21/32	1 1/32	1 1/32	21/32	23/32	23/32	-					
TS51750	19	1 21/32	1 1/16	1 1/16	23/32	1	3/4	-					
TS51827	21	1 21/32	1 3/16	1 3/16	21/32	1	27/32	-					

TSFS5005 5 Piece TURBOSOCKET® Salvage Socket Set on Clip Rail, SAE

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)
TS50750	3/4	TS50937	15/16
TS50812	13/16	TS50100	1
TS50875	7/8		

TSM5107 7 Piece TURBOSOCKET® Salvage Socket Set on Clip Rail, Metric

Contents Include:

Product Code	Size (MM)	Product Code	Size (MM)
TS51551	14	TS51709	18
TS51591	15	TS51750	19 (3/4")
TS51625	16 (5/8")	TS51827	21
TS51669	17		

Features

- Quickly and easily remove damaged or rounded nuts and bolts.
- Place socket on fastener and turn with ratchet, breaker bar or T-handle.
- Grip on fastener tightens as more torque is applied.
- No hammering is required to install socket over fastener.
- Use on all types of standard nuts and bolts as well as studs, pipe nipples, and corroded auto and marine fasteners.
- May be used for "best fit" on metric and fractional fasteners.
- May be used with air or electric impact wrench for extra speed and turning power.



1/2" DRIVE STANDARD LENGTH HEX BIT SOCKETS, SAE

High-Polished Chrome Finish

Product Code	Size (Inches)	Socket Length (Inches)	Socket Outside Diameter (Inches)	Overall Length (Inches)	Replacement Bit Product Code
SA-8A	1/4	1 1/2	29/32	2 1/4	BITH08-05
SA-10A	5/16	1 1/2	29/32	2 1/4	BITH10-05
SA-12A	3/8	1 1/2	29/32	2 1/4	BITH12-03
SA-16A	1/2	1 1/2	31/32	2 1/4	BITH16-01
SA-18A	9/16	1 9/16	1 1/16	2 1/4	BITH18-01
SA-20A	5/8	1 25/32	1 1/4	2 1/4	BITH20-01



SA-16A



WSSS-6RC

WSSS-6RC 6 Piece Hex Bit Socket Set on Clip Rail

Contents Include:

Product Code	Size (Inches)	Product Code	Size (Inches)
SA-8A	1/4	SA-16A	1/2
SA-10A	5/16	SA-18A	9/16
SA-12A	3/8	SA-20A	5/8

Features

- High-polished chrome finish socket cleans easily.
- Two piece design allows bits to be replaced easily.



1/2" DRIVE

SOCKETS AND DRIVE TOOLS